

Thrust Ball & Roller Bearing



Boundary dimensions(mm)				Basic load ratings(kN)		Speed (rpm)	Mass (Kg)	Bearing No.
d	D	T	rs min	Ca	Coa	Oil	(Approx.)	
150	215	39	1.5	340	1,340	1,800	4.56	29230
160	225	39	1.5	360	1,460	1,700	4.88	29232
170	240	42	1.5	425	1,770	1,600	6.02	29234
180	250	42	1.5	450	1,920	1,600	6.27	29236
190	270	48	2	530	2,230	1,400	8.8	29238
200	280	48	2	535	2,300	1,400	9.14	292
85	150	39	1.5	265	820	2,300	2.94	29317
90	155	39	1.5	285	915	2,300	3.08	29318
100	170	42	1.5	345	1,160	2,100	3.94	29320
110	190	48	2	445	1,500	1,800	5.78	29322
120	210	54	2.1	535	1,770	1,600	7.92	29324
130	225	58	2.1	615	2,100	1,500	9.76	29326
140	240	60	2.1	685	2,360	1,400	11.4	29328
150	250	60	2.1	675	2,390	1,400	12	29330
160	270	67	3	820	2,860	1,300	15.9	29332
170	280	67	3	855	3,050	1,200	16.6	29334
180	300	73	3	995	3,600	1,100	21.2	29336
190	320	78	4	1,150	4,250	1,100	26	29338
200	340	85	4	1,280	4,600	980	31.9	29340
60	130	42	1.5	283	805	2,600	2.78	29412
65	140	45	2	330	945	2,400	3.44	29413
70	150	48	2	365	1,040	2,200	4.19	29414
75	160	51	2	415	1,190	2,100	5.07	29415
80	170	54	2.1	460	1,380	1,900	6.09	29416
85	180	58	2.1	490	1,480	1,800	7.2	29417

90	190	60	2.1	545	1,680	1,700	8.38	29418
100	210	67	3	685	2130	1,500	11.5	29420
110	230	73	3	845	2,620	1,400	15	29422
120	250	78	4	975	3,050	1,300	18.6	29424
130	270	85	4	1,080	3,550	1,200	23.7	29426
140	280	85	4	1,110	3,750	1,200	25.2	29428
150	300	90	4	1,280	4,350	1,100	30.5	29430
160	320	95	5	1,500	5,150	1,000	37	29432
170	340	103	5	1,660	5,750	940	45	29434
180	360	109	5	1,840	6,200	890	52.9	29436
190	380	115	5	2,010	6,800	840	62	29438
200	400	122	5	2,230	7,650	790	73.3	29440

<http://www.bearing-fastener.com>